IN THE CLAIMS:

1. (Original) A method for implementing lighting by utilizing a lighting fixture having a plurality of laterally-spaced light source locations and corresponding lateral reflector positions, the method comprising selectively installing a reflector of a first type or a second type in respective ones of the plurality of lateral reflector positions,

wherein the first type reflector has a greater uplighting capacity compared to the second type reflector,

whereby the selectively installing determines a proportion of uplight versus downlight.

2. (Original) The method of claim 1 wherein the lighting fixture includes at least one socket at each of the plurality of lateral reflector positions, the method further comprising providing a switch member for connecting or disconnecting electricity to selected ones of the plurality of sockets.

3. (Currently Amended) The method of claim 1 further comprising interchanging a reflector of the first type and a reflector of the second type in at least one of the reflector positions.

4. (Original) The method of claim 1 further comprising referring to a chart for selecting between the first type reflector and the second type reflector for installation at a given one of the plurality of reflector positions.

5. (Original) The method of claim 4 wherein the chart is based on the number of lateral reflector positions and the respective translucences of the first type reflector and the second type reflector.

6. (Original) The method of claim 4 wherein the chart is based on lighting requirements for given areas within a facility.

7. (Original) The method of claim 4 wherein the chart is based on a number and proximity of other lighting fixtures.

8. (Original) The method of claim 4 wherein the chart is based on operational logic of at least one motion sensor.

9. (Original) The method of claim 4 wherein the chart is based on at least one lighting switch pattern being implemented for the plurality of reflector positions.

10. (Original) The method of claim 4 wherein the chart is based on at least one lighting switch pattern being implemented for a plurality of lighting fixtures.

11. (Original) The method of claim 4 wherein the chart is a program product implemented on a computer.

12. (Original) A method for implementing lighting comprising:

providing a lighting fixture having a plurality of lateral reflector positions; and

providing a plurality of reflectors of a first type and a second type, the reflectors for being selectively installed in respective ones of the plurality of lateral reflector positions,

wherein the first type reflector has a greater uplighting capacity compared to the second type reflector, and wherein selective installation of the reflectors determines a proportion of uplight versus downlight.

13. (Original) The method of claim 12 further comprising providing a chart that is referenced for selecting between the first type reflector and the second type reflector for installation at a given one of the plurality of reflector positions.

14. (Original) The method of claim 13 wherein the chart is based on the number of lateral reflector positions and the respective translucences of the first type reflector and the second type reflector.

15. (Original) A method for achieving a desired proportion of uplight versus downlight, the method comprising providing a program product operative for selecting between a first type reflector and a second type reflector for installation at a given one of a plurality of reflector positions,

wherein the first type reflector has a greater uplighting capacity compared to the second type reflector.

16. (Original) The method of claim 15 wherein the program product is adaptable to assist the selecting according to a user input that includes at least one of:

identifying component parts in the fixture;
identifying operational parameters of the fixture;
identifying lighting requirements for given areas to be lighted;
identifying a number, type, illumination level and/or proximity of other lighting fixtures;
identifying an implementation being used in conjunction with a motion sensor; and
identifying lighting switch patterns.

17. (Original) The method of claim 16 wherein the implementation being used in conjunction with a motion sensor includes a time delay for disconnecting an electrical connection to the fixture.